BCS-L-EIP15FCR3L3-AI1

Index: **11987** GTIN13/EAN13: 5904890712300
URL: https://bcs.pl/gb/5mpx/3815-bcs-l-eip15fcr3l3-ai1-5904890712300.html

BCS-L-EIP15FCR3L3-AI1

Product Details

Product	BCS-L-EIP15FCR3L3-AI1
Brand	BCS LINE
Camera type	Dome
Resolution	5 Mpx
Sensor	1/2.7'' CMOS
Scanning system	Progressive Scan
Pixels	2960(H)×1688(V)
RAM	256MB
ROM	128MB
Lens	fixed
Focal length	2.8 mm
Aperture	F1.6
Focus	fixed
Iris	fixed
Digital zoom	16×
Angle of view	H :111° V: 58° D: 132°
DORI	Detect 64m/ Observe 25m/ Recognize 13m/ Identify 6m
Min illumination	0.007Lux(Color,F1.6,30IRE) 0.0007Lux(F1.6,B/W,30IRE) 0Lux(IR)
S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
Image rotate	Mirror, Flip 0°/90°(corridor mode)/180°/270°
Stream support	2
Resolutions	5M(2960×1668) /4M(2880×1620)(2688×1520)(2560×1440) /3M(2304×1296)(2048×1536) /2M(1920×1080) /720P(1280×720) /D1(704×576/704×480) /VGA(640×480) /CIF(352×288/352×240)
Main stream	2960×1668(1~20fps) 2688×1520(1~25/30fps)
Second stream	704×576(1~25fps) 704×480(1~30fps)
Bitrate	H.264: 32 Kbps~8192 Kbps H.265: 12 Kbps~8192 Kbps
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Day/night	ICR mechanical infrared filter
Illuminator type	IR LED + WhiteLight
IR range	30m
WhiteLight range	30m
NightColor	Yes
Microphone	Yes
Audio compression	G.711A / G.711Mu / G.726 / PCM
Storage	FTP, SFTP
Memory card slot	microSD 256GB

Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Boujour
Power supply type	12V DC / PoE(802.3af)
Power consumption	max 5.4W
Housing color	White
IP class	IP67
Working environment	-40°C~+55°C max 95% RH
Dimensions	Ø106×94mm
Weight	0.39 kg
Casing	Metal
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analisis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - SMD - Smart Motion Detection	SMD Plus

BCS-L-EIP15FCR3L3-AI1

Accessories

BCS-UD2

BCS-UD3

BCS-L-ADMM

BCS-L-UD2

BCS-L-AT48

BCS-L-AT135(2)