

BCS-L-EIP25FSR5-Ai2



Index: 11539

GTIN13/EAN13: 5904890709416

URL: <https://bcs.pl/gb/5mpx/3559-bcs-l-eip25fsr5-ai2-5904890709416.html>

BCS LINE



Product Details

Product	BCS-L-EIP25FSR5-Ai2
Brand	BCS LINE
Camera type	Dome
Resolution	5 Mpx
Sensor	1/2.7" CMOS
Scanning system	Progressive Scan
Pixels	2960(H)×1688(V)
RAM	1GB
ROM	4GB
Lens	fixed
Focal length	2.8 mm
Aperture	F1.6
Focus	fixed
Iris	fixed
Digital zoom	16×
Angle of view	H :111° V: 58° D: 132°
DORI	Detect 64m/ Observe 25m/ Recognize 13m/ Identify 6m
Min illumination	0.0009Lux(Color,F1.6,30IRE) 0.0005Lux(B/W,F1.6,30IRE) 0Lux(IR)
S/N ratio	56dB

White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
Defog	Electronic
Image rotate	Mirror, Flip 0°/90°/180°/270°
Stream support	4
Resolutions	5M(2960×1668)(2880×1620) / 4M(2688×1520)(2560×1440) / 3M(2048×1536)(2304×1296) / 2M(1920×1080) / 1.3M(1280×960) / 720P(1280×720) / D1(704×576/704×480) / VGA(640×480) / CIF(352×288/352×240)
Main stream	2960×1668(1~25/30fps)
Second stream	704×576/704×480(1~25/30fps)
Third stream	1920×1080(1~25/30fps)
Fourth stream	1280×720(1~25/30fps)
Bitrate	H264: 32Kbps~16384Kbps H265: 12Kbps~11776Kbps
Video compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG / Ai Coding
Day/night	ICR mechanical infrared filter
Illuminator type	IR LED
Illuminator	50m
Microphone	Yes
Audio in	1
Audio out	1
Audio compression	G.711A / G.711Mu / G.723 / G.726 / PCM
Alarm in	1
Alarm out	1
Memory card slot	microSD 512GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	8
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP, P2P
Power supply type	12VDC / 24VAC / PoE(802.3af) / ePoE
Power consumption	max 8.3W
Housing color	White
IP class	IP67
Working environment	-40°C~+60°C max 95% RH
Dimensions	Ø106×94mm
Weight	0.5 kg
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Intrusion, crossline, fast moving, loitering, people gathering, parking detection
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion and fast moving reduces false alarms
Ai - Smart object detection	Intelligent detection missing/abandoned objects
Ai - Face detection	Face detection and tracking, snapshot, attributes and expression recognition
Ai - People counting	People counting for intrusion and crossline, counting people in/out/stay in, queue management, generate and export reports in periods of time
Ai - Metadata	People attributes (gender, clothes, color, bag, hat, umbrella), face attributes (gender, age, expression, glasses, mask, beard), vehicle attributes (type, color, logo, seat belts, smoking, calling)

Ai - Heat map

Recording the movement of objects over a period of time, statistics of the time density of movement presented graphically in red/blue color tones

Ai - SMD

SMD 3.0

Accessories



BCS-ADMM



BCS-AT135



BCS-AT48



BCS-UDU